

February 1991

EFFECTIVENESS OF A VERTICAL 3-WIRE ELECTRIC FENCE MODIFIED WITH ATTRACTANTS OR REPELLENTS AS A DEER EXCLOSURE

Don M. Jordan Jr.

U. S. Fish and Wildlife Service, New York Cooperative Fish and Wildlife Research Unit, Cornell University, Ithaca, NY

Milo E. Richmond

U. S. Fish and Wildlife Service, New York Cooperative Fish and Wildlife Research Unit, Cornell University, Ithaca, NY

Follow this and additional works at: <http://digitalcommons.unl.edu/ewdcc5>



Part of the [Environmental Health and Protection Commons](#)

Jordan, Don M. Jr. and Richmond, Milo E., "EFFECTIVENESS OF A VERTICAL 3-WIRE ELECTRIC FENCE MODIFIED WITH ATTRACTANTS OR REPELLENTS AS A DEER EXCLOSURE" (1991). *5 - Fifth Eastern Wildlife Damage Control Conference (1991)*. 24.

<http://digitalcommons.unl.edu/ewdcc5/24>

This Article is brought to you for free and open access by the Eastern Wildlife Damage Control Conferences at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in 5 - Fifth Eastern Wildlife Damage Control Conference (1991) by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

EFFECTIVENESS OF A VERTICAL 3-WIRE ELECTRIC FENCE MODIFIED WITH ATTRACTANTS OR REPELLENTS AS A DEER EXCLOSURE

DON M. JORDAN, JR., U. S. Fish and Wildlife Service, New York Cooperative Fish and Wildlife Research Unit, Cornell University, Ithaca, NY 14853-3001

MILO E. RICHMOND, U. S. Fish and Wildlife Service, New York Cooperative Fish and Wildlife Research Unit, Cornell University, Ithaca, NY 14853-3001

Abstract: We conducted experiments with behavioral conditioning of white-tailed deer (*Odocoileus virginianus*) using a 3-wire, electrified fence modified with either an attractant or a repellent in order to test the idea that an attractant or repellent coupled with an electric shock, would be a more effective deterrent than a random shock or no shock at all. Exclosures measuring 6 x 6 m with 3 wires at heights of 50, 100, and 150 cm were established at 2 study sites in Tompkins County, New York. Each site contained 4 exclosures which were either nonelectrified (control), electrified, electrified with an attractant, or electrified with a deer repellent. We baited each exclosure with fresh apples to ensure visitation by deer. All exclosures were monitored daily to determine deer visitation, disappearance of apples, and to measure fence voltage. Data from 116 days indicate that the electric fence with a repellent excluded deer most effectively. Deer penetrated this type of exclosure only once. Electricity and attractant ranked second, and electricity alone ranked third in effectiveness for excluding deer. The control was the least effective barrier (37 encroachments).

Proc. East. Wildl. Damage Control Conf. 5:44-47. 1992

Increasing human populations, urbanization of rural areas, and increasing populations of white-tailed deer cause more frequent interactions between humans and deer. This increase in interactions corresponds with an increase in deer damage incurred by fruit growers, nurserymen, and other groups (McAninch and Fargione 1987). Damage and economic losses sustained by farmers (Hyngstrom and Craven 1988), orchardists (Phillips et al. 1987, Purdy et al. 1987), nursery growers (Sayre and Decker 1990), and even gardeners and ornamental plant owners (Sayre and Decker 1990) have brought about the need for improved deer control techniques.

Little work has been done combining electric fencing with deer repellents or attractants. Separately, fencing and repellents have been found to reduce damage, and perhaps together they have a synergistic effect. We hypothesize that the addition of a repellent to an electric fence would double the negative reinforcement for deer. The repellent itself may cause the deer to avoid the fence. However, if a deer does attempt to enter the fence and receives a shock, the combination of the repellent and the shock may cause the deer to recognize and avoid the fence in the future. Coupling the electric shock with an attractant, to ensure that the encroaching deer receives the shock, may also enhance fence effectiveness. Peanut butter was used as an attractant to encourage deer to touch the electric wires with sensitive parts of their bodies (i.e., their tongue or nose). This, we hypothesize, results in a sufficiently severe shock for deer, and would cause conditioned animals to avoid fenced areas in the future. The use of peanut butter has been found effective with single-wire fences exposed to light deer pressure (Kinsey 1976, Porter 1983, Hyngstrom and Craven 1988), and may therefore enhance the effectiveness of the 3-wire design. We report here on the testing of the 3-wire electric fence with attractants and with repellents to determine its effectiveness as a deer exclosure.

STUDY AREA

Two sites in the Town of Dryden, Tompkins County, New York were selected for this fencing study. Site 1 was in Varna, a rural area 4 km east of the City of Ithaca, southeast of Cayuga Lake. The exclosures were in a 16-ha field owned by Cornell University. The field was used primarily for experimental vegetable crops, and was bordered on one side by County Route 366, and by a mixed hardwood-conifer woodlot and Fall Creek on the other sides. Hunting was not allowed in the bordering woodlots.

Site 2 was in Ellis Hollow, another rural area about 5 km southeast of Ithaca and 3 km southeast of the Varna site. Exclosures were in a privately-owned 3-ha field of goldenrod (*Solidago* spp.) and red-osier dogwood (*Cornus stolonifera*). The field contained a pond, was bordered by county roads to the north and west, and a mixed hardwood-conifer woodlot to the south and east. The area immediately surrounding the field provided excellent deer cover. Private ownership greatly limited hunting.

The density of deer in the study area is not known. The New York State Department of Environmental Conservation (DEC) uses buck-take/km² as their primary index for population estimates. For the 250-km² Town of Dryden, which encompasses both study sites, the average buck-take from 1985-1989 was 1.2 bucks/km².

Although information about buck harvest at the Varna site was not available it would seem that deer numbers in this area were at least as high as the town average. In reality, deer numbers were likely higher because of the ideal mix of cover and the lack of hunting pressure. Landowner data on deer take from the Ellis Hollow site suggest that deer densities in this area (3.6 bucks/ha, n = 22 years) were higher than the rest of the

town. A series of pellet-count transects were conducted at Ellis Hollow during April 1990, and an average of 89.3 pellet groups/ha (SE = 22.3, n = 14 transects) were found. Deer sign (including tracks, runs, and fecal pellets) and deer sightings (during the day and at night using spotlights) indicated that deer frequented both study sites. Although actual deer numbers were not known, a combination of the population indices and personal sightings indicate that there were medium-to-high deer numbers near the enclosures.

METHODS

Fencing efforts began in the summer of 1990. Four 6 x 6 m enclosures were established at each of the 2 study sites. Exclosures were randomly selected to receive 1 of 4 treatments: (1) no electricity (control), (2) electricity, (3) electricity and an

attractant, or (4) electricity and a repellent. The enclosures were

Vegetation inside and 1 m around each plot was cut with a law

and plastic corner insulators, 3 wires were connected to the posts at

lower wires were added to the fences at heights of 10 and 25 cm to

wires provided little physical barrier to the deer, but were necessary to

A 1 x 1 m area was dug in the center of each plot, and the soil was

3 top wires on all 4 sides of each enclosure. These strips provided a

used as an attractant, and an experimental deer repellent call

"Jersey" (Savre and Richmond 1991) was used as a repellent

All wires of the electric fences were powered with 6-volt solar-powered fence chargers. Fence-line voltage was mea

sured daily with a hand-held Voltmeter. Twelve apples were placed in the center of each plot. No lag time was permitted between presentation of bait and electrification of the fence prevent

December of 1990, and from early May to mid-August of 1991 the enclosures were visited daily to record the number of missing or damaged apples, and to note evidence of encroachment by deer or small mammals (i.e., tracks, scat, hair, fence

damage, apple damage, sightings, etc.). The study period encompassed 116 days of baited plot exposure (any day in which apples were available to deer). All missing or damaged apples were replaced daily, and plot centers were raked to clear away old tracks and keep the soil friable.

Vegetation was trimmed periodically using a lawn mower and weed whip. Fresh peanut butter and Jersey were placed on the cloth every 3-4 weeks to ensure that they continued to act as attractants or repellents.

RESULTS

The electric fence with the repellent Jersey most effectively excluded deer, as this design was only penetrated once (0.9% of total exposure days, Table 1). The electric fence with the peanut butter attractant was second most effective, experiencing only 9 (7.8% of total exposure days) encroachments. The electric fence alone ranked third most effective, as deer penetrated this design 13 times (11% of total exposure days). As expected, the least effective fence was the nonelectrified control. Deer penetrated the 2 control plots approximately 32% of the days. More than 300 apples were removed by deer during the 37 known instances of deer encroachment.

Table 1. Deer encroachment by fence design at study sites near Ithaca, New York, 1990-91.

Fence Design	Days of Plots	Instances of Deer Exposure	Damage	Apples taken by Deer
Control	2	116	37	328
Electric	2	116	13	79
Attractant & Electric	2	116	9	59
Repellent & Electric	2	116	1	8

*P < 0.01, X² = 32.27, 3df.

Deer entered the control enclosures more frequently than expected (JCS = 32.27, 3 df, P < 0.01), and deer penetrated the electric fences with Jersey less frequently than expected (X² = 13.07, 3 df, P < 0.01). Deer penetrated the electric fence alone or the fence with peanut butter as often as expected.

The addition of 2 lower electrified wires kept out some

small mammals, but were not an absolute barrier. The nonelectrified fence had little effect, as 560 apples (20.1% of all apples placed in both enclosures) were removed or damaged by small mammals. The 3 electrified fence designs reduced encroachment by small mammals. Only 385 (13.8%) apples were damaged or removed from enclosures treated with electricity and peanut butter, 330 (11.9%) from enclosures with electric fences without attractant or repellent, and 210 (7.5%)

from enclosures with electricity and Jersey.

DISCUSSION

Fencing has been one of the most effective controls for deer damage. Previously, most fencing efforts focused on conven

tional nonelectrified, woven-wire designs (Ellingwood et al. 1985). The most effective fence has been the 2.4-m vertical,

woven-wire design (Caslick and Decker 1979, McAninch and Winchcombe 1981, Craven 1983). Although this design pro

vides a formidable barrier to deer, the predominant objection to conventional fencing techniques has been high construction costs (Table 2). According to Ellingwood and McAninch (1984), construction of an 2.4-m woven-wire fence costs \$15.88 per linear meter (adjusted to 1991 prices). Consequently, conventional fences in areas of intensive agriculture, such as orchards or private gardens, have been limited (Harder 1968, Craven 1983). Furthermore, its large size and great visual impact makes an 2.4 m fence impractical for homeowners and gardeners.

Table 2. Prices and cost-effectiveness of basic deer fencing designs compared to the vertical 3-wire electric fence.'

Design	Cost'linear m	Level of deer pressure at which fence is cost-effective
2.4-m woven-wire nonelectric	\$15.88	High
7-Strand slanted electric fence	6.30	Moderate-high
Vertical 5-wire electric fence	3.25	Moderate-high
Vertical 3-wire electric fence	2.59	?

' Costs from Ellingwood and McAninch (1984), adjusted to 1991 prices.

Recent developments in fencing technology, including high-tensile wire and powerful, dependable fence chargers, have increased the popularity of electric fences. This, coupled with improved designs, has increased the efficacy of electrical fencing and provided the public with a variety of control options. One such design, the 7-strand slanted fence (Ellingwood et al. 1985), successfully excludes deer at high deer pressure (McAninch 1980, McAninch and Winchcombe 1981). With a construction cost of \$6.30 per linear meter (Table 2), this fence is much less expensive than the 2.4-m woven-wire fence. However, its spacious and complex design are impractical for homes and gardens. The vertical 5-wire fence (Ellingwood et al. 1985), also known as the Penn State electric fence, has been an effective deer enclosure (Palmer et al. 1983, Palmer et al. 1985, Kochel and Breneman 1987). Low cost of \$3.25 per linear meter (Table 1) and easy construction have increased the popularity of the 5-wire fence with homeowners. In spite of recent improvements in design and materials, fencing costs must be further reduced for practical use by the nursery owner, home gardener, and commercial vegetable grower.

The vertical, 3-wire electric fence at \$2.59 per linear meter (Table 2) is less expensive than the 5-wire fence. Its simple structure is practical for use by ornamental plant owners and gardeners. At medium to high deer pressures, the 3-wire design with attractants or repellents appeared to provide an effective deer enclosure.

The nonelectric fence was the least effective deer excluder either crawled under, went through, or jumped over it little difficulty. The addition of electricity clearly increased effectiveness of the design. A possible drawback of electric alone is that many times deer going through the fence contact the wire with insensitive parts of their body (i.e., n back, or chest), resulting in a shock too mild to deter the animal (McKillop and Sibly 1988). In addition, deer that recently electrical shocks to random parts of their body may not associate the pain with the fence, and as a result, may experience li aversive conditioning.

The number of deer encroachments into the electric' alone fences and electricity-plus-peanut-butter fences were statistically different in this study. However, the addition of peanut butter may create an association between the pain the shock and the fence, causing deer to avoid the fence in future encounters. The fact that 9 instances of encroachment occur, suggests that some deer did not investigate the peanut butter and simply entered the fence. Another possible explanation is that some deer that did receive a shock by investigation the peanut butter associated that pain only with the peanut butter and penetrated the fence in the future avoiding the peanut butter.

The electric fence with the repellent Jersey was the most effective and was encroached upon less frequently. Because we do not have observations of deer encountering any of these fences, we can only speculate as to how they work. If deer avoid the fenced area altogether because of the odor from the repellent, then this reduces the possibility of random crossings of the fence.

The combination of electricity and repellent may be effective because the presence of the electricity provides a second level deterrent. Without electricity, a deer that ignores the repellent would have little trouble crossing the fence. However, a deer that initially ignores the repellent and then receives a shock while trying to enter the fence may avoid the fence in the future because of the dual aversive conditioning.

Deer appeared to exhibit a conditioned avoidance of the fences equipped with the peanut butter and Jersey. McKillop and Sibly (1988) state that most animals can learn an immediate and long-lasting avoidance of objects associated with unpleasant experiences. It would be useful to continue studies of learned behavior in both captive and free-ranging deer, and attempt to take advantage of this conditioned avoidance phenomenon. Studies of multiple-cueing, or simply the identification of key signals that warn deer (i.e., flagging, unusually-shaped objects, odor-based repellents, etc.) may prove quite fruitful in a search for new deer management strategies.

MANAGEMENT IMPLICATIONS

The vertical, 3-wire electrified fence modified with the addition of a deer repellent provided an effective barrier to deer encroachment at medium-to-high deer densities. With its small

visual impact, simple design, and relatively-low construction costs, the 3-wire fence could be further developed as an inexpensive and viable control of damage in many situations, especially those faced by homeowners and gardeners. Although the use of electrified fencing may be inappropriate in areas frequented by humans, particularly children, further investigation into the duration of conditioned-fence-avoidance behavior by deer may reduce the amount of time necessary to keep the fence electrified.

LITERATURE CITED

- Caslick, J. W., and D. J. Decker. 1979. Economic feasibility of a deer-proof fence for apple orchards. *Wildl. Soc. Bull.* 7:173-175.
- Craven, S. R. 1983. Deer. Pages D23-D33 in R. M. Timm, ed. *Prevention of wildlife damage*. Great Plains Agric. Council, Univ. of Nebraska, Lincoln. 625pp.
- Ellingwood, M. R., and J. B. McAninch. 1984. Deer damage control in orchards and vineyards. Final Rep., Proj. No. 4946. N.Y. Dep. of Agric. and Markets, Albany. 25pp.
- and M. J. Fargione. 1985. Current status of deer fencing in the Northeast. *Proc. East. Wildl. Damage Control Conf.* 2:180-185.
- Harder, J. D. 1968. A literature review on orchard damage by deer. *Colo. Dep. Game, Fish, Parks Spec. Rep. No. 12*, 22pp.
- Hygnstrom, S. E., and S. R. Craven. 1988. Electric fences and commercial repellents for reducing deer damage in cornfields. *Wildl. Soc. Bull.* 16:291-296.
- Kinsey, C. L. 1976. Tests of two electric deer barrier forms. *Minn. Wildl. Res. Quart.* 36:122-138.
- Kochel, J., and R. Brennehan. 1987. Use and effectiveness of electric fencing in protecting clearcuts from deerbrowsing. Pages 118-122 in *Proc. Deer, Forestry, and Agric. Symp.: Interactions and Strategies For Management*, Allegheny Soc. of Amer. For., Warren, Pa. 183pp.
- McAninch, J. B. 1980. Recent advances in repellents and fencing to deter deer damage. *Proc. New England Hort. Soc.* 86:31-39.
- and R. J. Winchcombe. 1981. Deer damage control in orchards and vineyards in New York. *The N. Y. Botanical Garden, Cary Arboretum, Millbrook, N.Y.* 21pp.
- and M. J. Fargione. 1987. Characteristics of deer damage in selected plant industries of New York State. Final Rep., Proj. No. 4943. N.Y. Dep. of Agric. and Markets, Albany. 75pp.
- McCillop, I. G., and R. M. Sibly. 1988. Animal behaviour at electric fences and the implications for management. *Mammal Rev.* 18:91-103.
- Palmer, W. L., R. G. Wingard, and J. L. George. 1983. Deer damage control in Pennsylvania agriculture. *Proc. East. Wildl. Damage Control Conf.* 1:75-76.
- J. M. Payne, R. G. Wingard, and J. L. George. 1985. A practical fence to reduce deer damage. *Wildl. Soc. Bull.* 13:240-245.
- Phillips, M., C. G. Forshey, G. B. White, and M. E. Richmond. 1987. The economic impact of wildlife damage on Hudson Valley orchards. *Proc. East. Wildl. Damage Control Conf.* 3:66-82.
- Porter, W. F. 1983. A baited electric fence for controlling deer damage to orchard seedlings. *Wildl. Soc. Bull.* 11:325-327.
- Purdy, K. G., W. F. Siemer, G. A. Pomerantz, and T. L. Brown. 1987. Deer damage control preferences and use decisions of New York orchardists. *Proc. East. Wildl. Damage Control Conf.* 3:118-127.
- Sayre, R. W., and D. J. Decker. 1990. Deer damage to the ornamental horticulture industry in suburban New York: extent, nature and economic impact. *Human Dimensions Res. Unit Publ.* 90-1. *Dep. Nat. Resour., N.Y.S. Coll. Agric. and Life Sci., Cornell Univ., Ithaca, N.Y.* 75pp.
- and M. E. Richmond. 1991. Evaluation of a new deer repellent at suburban homesites. *Proc. East. Wildl. Damage Control Conf.* 5:38-43.